



# PPG LO-VEL<sup>®</sup> 29

## Flatting Agent – Non-Treated

COATINGS

PPG LO-VEL<sup>®</sup> 29 silica is a synthetic amorphous silicon dioxide flatting agent designed to reduce the gloss of coil coatings.

### Benefits

- Provides outstanding flatting efficiency at all viewing angles, including 85°
- Gives films a gloss:sheen ratio close to 1:1
- Easily incorporated and dispersed into solvent and waterborne coatings systems
- Low oil absorption and does not “body-up” paint excessively



### Applications

Metal furniture finishes  
Appliance finishes  
Coil coatings



Lo-Vel 29 Silica – Typical Properties	
Median Particle Size (laser light diffraction), $\mu\text{m}$	10
$\text{N}_2$ -BET Surface Area, $\text{m}^2/\text{g}$	150
DOA-Oil Absorption Number, $\text{mL}/100\text{g}$	215
Hegman Value	5
Fineness of Grind, $\mu\text{m}$	38
Moisture Content, %	$\leq 7.5$
pH	6.9

### Samples

Samples are available per request from customer service.

### Packaging

Standard packaging in small bags are unitized for shipping on pallets and stretch wrapped with clear plastic film. Please consult with customer service or your sales representative regarding additional packaging options including custom package sizes.

### Storage

To ensure product integrity, we recommend that our silica products be stored under dry, clean conditions, protected against exposure to direct sunlight and other substances, and used within 12 months of the date of manufacture. PPG silica products that are stored for more than one year from the date of manufacture should be tested for moisture content.

### Safety and Health Effects

We recommend that, before use, anyone using or handling this product thoroughly read and understand the information and precautions on the label, as well as in other product safety publications such as the Safety Data Sheet. Any health hazard and safety information contained herein should be passed on to your customers or employees, as the case may be. The products mentioned herein can be hazardous if not used properly. Like all potentially hazardous materials, this product must be kept out of the reach of children.

### Product Safety and Regulatory Information

For the latest product safety and regulatory information, please reference the Safety Data Sheets at [www.ppgsilica.com](http://www.ppgsilica.com).



**USA**  
PPG Silica Products  
440 College Park Drive  
Monroeville, PA 15146 USA

Customer Service: 1-800-243-6745  
Technical Service: 1-800-764-7369  
E-mail: [silicacustserv@ppg.com](mailto:silicacustserv@ppg.com)

**EUROPE**  
PPG Delfzijl Plant  
P.O. Box 181  
9930 AD Delfzijl, The Netherlands

Customer Service: +31-596-676710  
Technical Service: +31-596-676710  
E-mail: [csdelfzijl@ppg.com](mailto:csdelfzijl@ppg.com)

